



Technische specificaties print PRO vloervinyl DCOD printtapijt

Total thickness	ISO 24346 / EN 428		2.0 mm
Wear layer thickness	ISO 24340 / EN 429		0.7 mm
Commercial use	ISO 10874 / EN 685		34 very heavy
Industrial use	ISO 10874 / EN 685		43 heavy
Roll width	ISO 24341 / EN 426		3,95 m
Roll length	ISO 24341 / EN 426		± 25 m
Total weight	ISO 23997 / EN 430		2.8 kg/m ²
Dimensional stability	ISO 23999 / EN 434		≤ 0,40%
Furniture leg resistance	ISO 16581 / EN 424		no damage
Abrasion resistance	EN 660-2		group T
Delamination test (peel resistance)	ISO 24345		≥ 50N/50mm
Light fastness	ISO 105-B02		≥ 6
Flexibility	ISO 24344 / EN 435		ø 10 mm
Resistance to chemicals	ISO 26787 / EN 423		very good
Slip resistance	DIN 51130		R10
Impact sound improvement	ISO 717/2		ΔL _w 6 dB
Suitable for floor heating	EN 12667		Suitable
Castor chair continuous use	ISO 4918 / EN 425		Suitable (type wheel H)
Curling	ISO 23999		≤ 8mm

All PRO products meet the requirements of EN 14041

Reaction to fire	EN 13501-1		B _s -s1	
Slip resistance	EN 13893		DS - μ ≥ 0,60	
Body voltage	EN 1815		≤ 2 kV	
Thermal conductivity	EN 12524		0,14W/m-K	



This is illustrative by the choice of raw materials of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment. We are the leaders in terms of the implementation of clean renewable energy sources and we actively work towards the constant improvement of energy saving.



*) Please note that the data given could be imprecise and liable to modifications of a technical nature at any time. The information in these documents is valid from 01/01/2017 and M4Printing B.V. reserve the right to make changes at any moment without prior notice. Our technology is constantly evolving, so before carrying out any projects we encourage you to contact us to maintain our highest level of standards. **) Our products are classified as A+ for the emission of volatile substances inside air. (compulsive sanitary labelling in France since January 2012)

DCOD print-vloervinyl
Westerparallelweg 14 7951 LL Staphorst
0522-475702 e-mail: aanvraag@dcod-printtapijt.nl

Al onze producten worden duurzaam geproduceerd en gecertificeerd geleverd